

imageRUNNER ADVANCE C3500 III Series

Color | Low- to Mid-volume | Multifunction

Print up to 30 ppm (BW/color)

Scan up to 160 ipm (300 dpi) (BW/color, duplex)

Print up to 12" × 18"

2,300-sheet maximum paper capacity



Canon's comprehensive portfolio of imageRUNNER ADVANCE multifunction printers and integrated solutions can help **simplify** the end user experience and management of technology, better **control** sensitive information and print-related costs, and help ensure that technology investments proactively **evolve** with changing needs.



WORKFLOW EFFICIENCY

- 10.1" intuitive touchscreen with smartphone-like usability.
- A unique, customized experience tailored to individual preferences using My ADVANCE.
- Supports mobile solutions and integration with many popular cloud services like Google Drive!
- Scan and convert documents to searchable digital files in a variety of file formats.
- Integration with Canon and various third-party software with embedded application platform.



SECURITY

- Advanced standard security feature set to help safeguard sensitive information and assist in regulatory compliance.
- Integrates with existing, third-party Security Information and Event Management (SIEM) systems to help provide real-time comprehensive insights into potential threats to the network and printers.
- Technology to verify that the device boot process, firmware, and applications initialize without alterations or tampering.
- Security policy settings can be controlled with a dedicated password, configured from a central location, and exported to other supported devices.
- Control access to the device and specific features, using a host of flexible authentication methods—PIN code, user name/password, or card access.²



QUALITY AND RELIABILITY

- Canon's signature reliability and engine technologies help keep productivity high and minimize the impact on support resources.
- Outstanding imaging technologies and toner allow for consistently striking images, thanks to Canon's V² color profile.
- Designed to achieve maximum uptime with status notifications that help keep supplies replenished and intuitive maintenance videos for consumables replacement.
- imageRUNNER ADVANCE models have received many awards and recognition from leading industry analysts, often referencing strong reliability.



DEVICE AND FLEET MANAGEMENT

- Designed for quick, easy deployment.
- Remote diagnostics and parts life management for proactive maintenance and rapid fixes.
- Easy and intuitive to monitor device status and consumable levels, turn off devices remotely, observe meter readings, manage settings, and implement security policies.
- Common firmware and regular updates with Unified Firmware Platform (UFP) for continuous improvements and consistency across a fleet.



COST MANAGEMENT


- Track and assess print, copy, scan, and fax usage and allocate costs to departments or projects.
- Apply print policies and restrict usage by user to help reduce unnecessary printing and contribute to cost efficiency.
- Standard cloud-based solution provides a centralized dashboard with up-to-the-minute insights into printer activity.
- Upgrade to uniFLOW server or cloud-based solutions for full accounting and reporting for compatible Canon and third-party devices, pull printing, job routing, and powerful scan workflows.



SUSTAINABILITY

- A combination of fusing technologies and low-melting-point toner minimizes power requirements and helps achieve low energy consumption.
- Encourage environmentally conscious work practices by enabling multiple settings that can help save paper and energy.
- ENERGY STAR® certified and rated EPEAT® Gold³

CONFIGURATION OPTIONS



SPECIFICATIONS

Main Unit

Type

Color Laser Multifunctional

Core Functions

Standard: Print, Copy, Scan, Send, Store
Optional: Fax

Processor

Canon Dual Custom Processor (Shared)

Control Panel

10.1" TFT LCD WSVGA Color Flat-panel

Memory

3.0 GB RAM

Hard Disk Drive

Standard: 250 GB

Interface Connection

Network: 1000Base-T/100Base-TX/10Base-T,
Wireless LAN (IEEE 802.11 b/g/n)

Optional: NFC, Bluetooth Low Energy

Others
Standard: USB 2.0 x1 (Host), USB 3.0 x1 (Host),
USB 2.0 x1 (Device)

Optional: Serial Interface, Copy Control Interface

Paper Capacity (LTR, 20 lb. Bond)

Standard: 1,200 Sheets
Maximum: 2,300 Sheets

Paper Sources (LTR, 20 lb. Bond)

Standard: Dual 550-sheet Paper Cassettes, 100-sheet
Stack Bypass

Optional: Dual 550-sheet Paper Cassettes
(CASSETTE FEEDING UNIT-API)

Paper Output Capacity (LTR, 20 lb. Bond)

Standard: 250 Sheets
Maximum: 3,450 Sheets
(with External Finisher and Copy Tray)

Finishing Capabilities

Standard: Collate, Group
With Inner Collate, Group, Offset, Staple, Staple-Free
Finisher: Staple, Staple On Demand
With External Collate, Group, Offset, Staple, Booklet, Staple-
Finishers: Free Staple, Staple On Demand,
Hole Punch (Optional)

Supported Media Types

Paper Thin, Plain, Recycled, Color, Heavy,
Cassettes Pre-punched, Bond, Transparency,
(1/2): Envelope
Stack Bypass: Thin, Plain, Recycled, Color, Heavy,
Pre-punched, Labels, Bond, Coated,
Transparency, Tracing, Envelope

Cassette
Feeding Unit-API: Thin, Plain, Recycled, Color, Heavy,
Pre-punched, Bond, Transparency

Supported Media Sizes

Paper Letter, Executive, Statement-R, Envelope
Cassette 1: [ISO-C5], Custom Size (5-1/2" x 7-1/8"
to 11-3/4" x 8-1/2")

Paper Cassette 2: 12" x 18", 11" x 17", Legal, Letter, Letter-R,
Executive, Statement-R, Envelope
[No.10 (COM10), Monarch, DL], Custom Size
(5-1/2" x 7-1/8" to 12" x 18")

Stack Bypass: 12" x 18", 11" x 17", Legal, Letter, Letter-R,
Executive, Statement, Statement-R,
Envelope [No.10 (COM10), Monarch,
DL, ISO-C5], Envelope Custom Size
(3-7/8" x 3-7/8" to 12-5/8" x 18"),
Custom Size (3-7/8" x 5-1/2" to
12-5/8" x 18"), Free Size (3-7/8" x 5-1/2"
to 12-5/8" x 18")*

Cassette
Feeding Unit-API: 12" x 18", 11" x 17", Legal, Letter, Letter-R,
Executive, Statement-R, Custom Size
(5-1/2" x 7-1/8" to 12" x 18")

Supported Media Weights

Cassettes: 14 lb. Bond to 80 lb. Cover (52 to 220 g/m²)
Stack Bypass: 14 lb. Bond to 110 lb. Cover (52 to 300 g/m²)
Duplexing: 14 lb. Bond to 80 lb. Cover (52 to 220 g/m²)

Print/Copy Speed (BW and Color)

C3530i III: Up to 30 ppm (Letter); Up to 20 ppm
(Letter-R); Up to 15 ppm (Legal);
Up to 15 ppm (11" x 17")

C3525i III: Up to 25 ppm (Letter); Up to 20 ppm
(Letter-R); Up to 15 ppm (Legal);
Up to 15 ppm (11" x 17")

Warm-up Time

From Power On: Approx. 10 Seconds⁵
From Sleep: Approx. 10 Seconds⁶

Mode:
Quick Startup: Approx. 4 Seconds⁷
Mode:

Dimensions (W x D x H)

22-1/4" x 29-1/4" x 45-1/5" (565 mm x 742 mm x 1148 mm)⁸

Installation Space (W x D)

Basic: Stack Bypass + Cassette Drawers open:
38-1/2" x 44-1/4" (978 mm x 1123 mm)⁸

Fully
Configured: 63-3/4" x 44-1/4" (1620 mm x 1123 mm)⁹

Weight

Approx. 213.8 lb. (97 kg)¹⁰

Print Specifications

Print Resolution (dpi)

1200 x 1200, 600 x 600

Standard Page Description Languages

UFR II, PCL[®]6, Adobe[®] PS[®]3

Direct Print

Available from USB, Advanced Box, Remote UI,
and Web Access¹¹

Supported File Types

PDF, TIFF, JPEG, EPS, XPS

Printing from Mobile Devices and Cloud-based Services

A range of software and MEAP-based solutions are
available to provide printing from mobile devices or
Internet-connected devices and cloud-based services
depending on your requirements.

Fonts

PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts,
Andalé Mono WT J/K/S/T (Japanese,
Korean, Simplified and Traditional Chinese),¹²
Barcode Fonts¹³
PS fonts: 136 Roman

Operating System¹⁴

UFR II/PS: Windows[®]/Server 2008/Windows[®] 7/
Server 2008 R2/Server 2012/Windows 8.1/
Server 2012 R2/Windows 10/Server 2016,
MAC OS X (10.9 or later)

PCL: Windows/Server 2008/Windows 7/Server
2008 R2/Server 2012/Windows 8.1/Server
2012 R2/Windows 10/Server 2016

PPD: MAC OS X (10.3.9 or later), Windows 7/8.1/10

Copy Specifications

First-Copy-Out Time (LTR)

As fast as 5.9 seconds (BW)/8.2 seconds (Color)

Multiple Copies

Up to 999

Magnification

25%-400% (1% Increments)

Preset Reductions

25%, 50%, 64%, 73%, 78%

Preset Enlargements

121%, 129%, 200%, 400%

Basic Copy Features

Preset Reduction/Enlargement Ratios by Area, Paper
Setting, Previous Settings, Favorite Settings, Finishing, Two-
sided, Density Adjustment, Original Type Selection, Interrupt
Mode, Setting Confirmation/Cancel

Special Copy Features

Book to Two Pages, Two-sided Original, Finishing, Booklet,
Job Build, N on 1, Add Cover, Insert Sheets, Different-size
Originals, Density Adjustment, Original Type Selection,
Transparency Cover Sheets, Page Numbering, Copy Set
Numbering, Sharpness, Erase Frame, Secure Watermark,
Print Date, Shift, Gutter, Print & Check, Negative/Positive,
Repeat Images, Job Done Notice, Mirror Image, Copy ID
Card, Multi Sheet Feed Detection, Free Size Original, Adjust
One-Touch Color, Color Balance, Area Designation, Skip
Blank Pages

Scan Specifications

Type

Single-pass Duplexing Automatic Document Feeder¹⁵

Document Feeder Paper Capacity

150 Sheets (20 lb. Bond)

Document Feeder Supported Media Sizes

11" x 17", Legal, Letter, Letter-R, Statement, Statement-R,
Custom Size: 5" x 5-1/2" to 12" x 17" (128 mm x 139.7 mm to
304.8 mm x 431.8 mm)

Document Feeder Supported Media Weights

BW Original: 13 lb. Bond to 58 lb. Cover (50 to 157 g/m²)
Color Original: 17 lb. Bond to 58 lb. Cover (64 to 157 g/m²)

Platen Acceptable Originals

Sheet, Book, 3-Dimensional Objects [Height: Up to 2" (50mm),
Weight: up to 4.4 lb. (2kg)]

Platen Maximum Scanning Size

11-3/4" x 17" (297.0 mm x 431.8 mm)

Pull Scan

Color Network ScanGear2 for both Twain and WIA
Supported OS: Windows 7/8.1/10/
Server 2008/Server 2008 R2/
Server 2012/Server 2012 R2/Server 2016

Scan Resolution (dpi)

600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200,
200 x 100, 150 x 150, 100 x 100

Scan to Mobile Devices and Cloud-based Services

A range of solutions is available to provide scanning to
mobile devices and cloud-based services depending on
your requirements.

Scan Speed (LTR)

Single-sided Scanning (BW and Color):
80 ipm (300 dpi)/51 ipm (600 dpi)
Double-sided Scanning (BW and Color):
160 ipm (300 dpi)/51 ipm (600 dpi)

Send Specifications

Destination

Email/Internet Fax (SMTP), SMB v3.0, FTP, WebDAV, Mail
Box, Super G3 Fax (Optional), IP Fax (Optional)

Address Book

LDAP (2,000)/Local (1,600)/Speed Dial (200)

Send Resolution (dpi)

600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200,
200 x 100, 150 x 150, 100 x 100

Communication Protocol

File: FTP (TCP/IP), SMB v3.0, WebDAV
Email: SMTP, POP3

File Format

Standard: TIFF, JPEG, PDF (Compact, Searchable,
Apply Policy, Optimize for Web, PDF
A/1-b, Encrypted, Device Signature), XPS
(Searchable, Compact, Device Signature),
Office Open XML (PowerPoint, Word)
Optional: PDF (Trace & Smooth, User Signature),
XPS (User Signature)

Universal Send Features

Original Type Selection, Two-sided Original, Book to Two
Pages, Different-size Originals, Density Adjustment,
Sharpness, Copy Ratio, Erase Frame, Job Build, Delayed Send,
Preview, Job Done Notice, File Name, Subject/Message, Reply-
To, Email Priority, TX Report, Original Content Orientation,
Skip Blank Originals, Multi Sheet Feed Detection

Fax Specifications

Maximum Number of Connection Lines

2

Modem Speed

Super G3: 33.6 Kbps
G3: 14.4 Kbps

Compression Method

MH, MR, MMR, JBIG

Resolution (dpi)

400 x 400, 200 x 400, 200 x 200, 200 x 100

Sending/Recording Size

Statement-R to 11" x 17"

Fax Memory

Up to 30,000 Pages

Speed Dials

Max. 200

Group Dials/Destinations

Max. 199 Dials

Sequential Broadcast

Max. 256 Addresses

Memory Backup

Yes

Fax Features

Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density for Scanning, Sharpness, Copy Ratio, Erase Frame, Job Build, Sender's Name (TTI), Select Line, Selecting the Telephone Line, Direct Send, Delayed Send, Preview, Job Done Notice, TX Report, Multi Sheet Feed Detection

Store Specifications

Mail Box Simple (Number Supported)

100 User In-boxes, 1 Memory RX In-box, 50 Confidential Fax In-boxes, 30,000 Maximum Pages Stored

Advanced Box

Communication Protocol: SMB or WebDAV Supported

Client PC: Windows (Windows 7/8.1/10)

Concurrent Connections (Max.)

SMB: 64

WebDAV: 3 (Active Sessions)

Advanced Box Available Disc Space

Approx. 16 GB

Advanced Box Features

Authentication for Advanced Box Log-in, Sort Function, Printing a PDF File with a Password, imageWARE Secure Audit Manager Support

Memory Media

Standard: USB

Security Specifications

Authentication

Standard: Universal Login Manager, uniFLOW Online Express,¹⁶ User Authentication, Department ID Authentication, Access Management System, Device and Function Level Log-in uniFLOW

Optional:

Data

Standard: Trusted Platform Module (TPM), Hard Disk Password Lock, Hard Disk Drive Erase, Mail Box Password Protection, Hard Disk Drive Encryption (FIPS140-2 Validated), Verify System at Startup

Optional: Hard Disk Drive Removal, IEEE 2600.2 Common Criteria Certification, Data Loss Prevention (Requires uniFLOW)

Network

Standard: Encrypted Secure Print, IP/Mac Address Filtering, IPsec, TLS Encrypted Communication, SNMP V3.0, IEEE 802.1X, IPv6, SMTP Authentication, POP Authentication before SMTP, S/MIME, SIEM Integration

Document

Standard: Secure Watermark, Secure Print, Adobe LiveCycle® Rights Management ES2.5 Integration, Encrypted PDF, Encrypted Secure Print, Digital Signature, User Signatures, Document Scan Lock

Optional:

Environmental Specifications

Operating Environment

Temperature: 50 to 86 °F

Humidity: 20 to 80 % RH (Relative Humidity)

Power Requirements

C3530i III/ 120-127V AC 60 Hz, 7.5 A

C3525i III:

Plug (Main Unit)

C3530i III/ NEMA 5-15P

C3525i III:

Power Consumption

Maximum: Approx. 1,500 W

Standby: Approx. 42.9 W¹⁷

Sleep Mode: Approx. 0.8 W¹⁸

Typical Electricity Consumption (TEC) Rating

C3530i III: 1.2 kWh

C3525i III: 1.0 kWh

Standards

ENERGY STAR® Certified

Rated EPEAT® Gold³

Consumables

Toner

GPR-53 Toner¹⁹

Toner Yield (Estimated @ 5% Coverage)

Black: 36,000 Images

Color (C,M,Y):¹⁹ 19,000 Images

- ¹ Subscription to a third-party cloud service required. Subject to third-party cloud service providers' terms and conditions.
- ² Requires additional option.
- ³ For current EPEAT rating (Gold/Silver/Bronze), please visit www.epeat.net.
- ⁴ Heavy paper (95 to 110 lb. Cover) can be supported as follows: Standard format paper size (excluding SRA3), Custom size (3-7/8" x 5-1/2" to 12" x 18"). Free size (3-7/8" x 5-1/2" to 12" x 18")
- ⁵ Time from device power-on to when copy jobs can be programmed with Quick Start Up mode.
- ⁶ Time from exiting Sleep mode to when printing is operational.
- ⁷ Time from device power-on to when key operation can be performed on the touch screen.
- ⁸ Includes main unit and either Cassette Feeding Unit-API, or Cabinet Type-R.
- ⁹ Includes main unit and either Cassette Feeding Unit-API or Cabinet Type-R and Staple/Booklet Finisher-AAI.
- ¹⁰ Includes main unit, ADF consumables, and Cassette Feeding Unit-API.
- ¹¹ PDF print from Web sites is supported.
- ¹² Requires the optional PCL International Font Set-A1.
- ¹³ Requires the optional Barcode Printer Kit-D1.
- ¹⁴ Other operating systems and environments, including AS/400, UNIX, Linux and Citrix, may be supported. Some solutions are chargeable. SAP Device Types are available via the SAP Market Place. For more information, contact your sales representative.
- ¹⁵ Detect Feeder Multi Sheet Feed is supported.
- ¹⁶ No charge for this solution; however activation is required.
- ¹⁷ Reference value (measured one unit).
- ¹⁸ 0.8 W sleep mode not available in all circumstances due to certain settings.
- ¹⁹ GPR-53L Toner also available for Color (C, M, Y). Yield (estimated @ 5% coverage) is 8,500 images.

For detailed specifications and a comprehensive list of optional accessories, see the imageRUNNER ADVANCE C3500 III Series Specifications document.

USA.CANON.COM/SIMPLYADVANCED



As an ENERGY STAR® Partner, Canon U.S.A., Inc. has certified these models as meeting the ENERGY STAR energy efficiency criteria through an EPA recognized certification body. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. AirPrint and the AirPrint logo are trademarks of Apple Inc. Canon, imageRUNNER, imageWARE, imagePASS, and the GENUINE logo are registered trademarks or trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. Canon products offer certain security features, yet many variables can impact the security of your devices and data. Canon does not warrant that use of its features will prevent security issues. Nothing herein should be construed as legal or regulatory advice concerning applicable laws; customers must have their own qualified counsel determine the feasibility of a solution as it relates to regulatory and statutory compliance. All other referenced product names and marks are trademarks of their respective owners. All printer output images are simulated. All features presented in this brochure may not apply to all Series and/or products and may be optional; please check with your Canon Authorized Dealer for details. Products shown with optional accessories. Canon U.S.A. does not provide legal counsel or regulatory compliance consultancy, including without limitation, Sarbanes-Oxley, HIPAA, GLBA, Check 21 or the USA Patriot Act. Each customer must have its own qualified counsel determine the advisability of a particular solution as it relates to regulatory and statutory compliance. Specifications and availability subject to change without notice. Not responsible for typographical errors. ©2019 Canon U.S.A., Inc. All rights reserved.

Federal Law prohibits copying of certain documents. Violators may be subject to penalties. We suggest that you check with your own legal counsel. Canon U.S.A., Inc. and Canon Canada, Inc. intend to cooperate with Law Enforcement Agencies in connection with claims of unauthorized copying.



0216W216
0219-iRAC3500IIISRSB-7M-DJD

To learn about Canon's many awards, visit usa.canon.com/awards.

