

imageRUNNER ADVANCE 4500 III Series

Black-and-White | Mid-Volume | Multifunction

Print up to 51 ppm (BW)

Scan up to 160 ipm (300 dpi) (BW/color, duplex)

Print up to 11" x 17"

6,350-sheet maximum paper capacity

Canon's comprehensive portfolio of imageRUNNER ADVANCE multifunction printers and integrated solutions can help **simplify** the end user experience and management of technology; better **control** sensitive information and print-related costs; and help ensure that technology investments proactively **evolve** with changing needs.



WORKFLOW EFFICIENCY

- 10.1" intuitive touchscreen with smartphone-like usability.
- A unique, customized experience tailored to individual preferences with My ADVANCE.
- Supports mobile solutions and integration with many popular cloud services like Google Drive and Box.¹
- Scan and convert documents to searchable digital files in a variety of file formats.
- Integration with Canon and various third-party software with embedded application platform.



SECURITY

- Advanced standard security feature set to help safeguard sensitive information and assist in regulatory compliance.
- Integrates with existing, third-party Security Information and Event Management (SIEM) systems to help provide real-time comprehensive insights into potential threats to the network and printers.
- Technology to verify that the device boot process, firmware, and applications initialize without alterations or tampering.
- Security policy settings can be controlled with a dedicated password, configured from a central location, and exported to other supported devices.
- Control access to the device and specific features, using a host of flexible authentication methods—PIN code, user name/password, or card access.²



COST MANAGEMENT

- Track and assess print, copy, scan, and fax usage and allocate costs to departments or projects.
- Apply print policies and restrict usage by user to help reduce unnecessary printing and contribute to cost efficiency.
- Standard cloud-based solution provides a centralized dashboard with up-to-the-minute insights into printer activity.
- Upgrade to uniFLOW server or cloud-based solutions for full accounting and reporting for compatible Canon and third-party devices, pull printing, job routing, and powerful scan workflows.



DEVICE AND FLEET MANAGEMENT

- Designed for quick, easy deployment.
- Remote diagnostics and parts life management for proactive maintenance and rapid fixes.
- Easy and intuitive to monitor device status and consumable levels, turn off devices remotely, observe meter readings, manage settings, and implement security policies.
- Common firmware and regular updates with Unified Firmware Platform (UFP) for continuous improvements and consistency across a fleet.



QUALITY AND RELIABILITY


- Canon's signature reliability and engine technologies help keep productivity high and minimize the impact on support resources.
- Outstanding imaging technologies and toner allow for crisp text and consistent images in rich black-and-white tones.
- Designed to achieve maximum uptime with status notifications to help keep supplies replenished and intuitive maintenance videos for consumables replacement.



SUSTAINABILITY

- A combination of fusing technologies and low-melting-point toner minimizes power requirements and helps achieve low energy consumption.
- Encourage environmentally-conscious work practices by enabling multiple settings that can help save paper and energy.
- ENERGY STAR® certified and rated EPEAT® Gold.³

CONFIGURATION OPTIONS



Not Shown

- Inner 2/3-Hole Puncher-C1 (for Inner Finisher-J1)
- 2/3-Hole Puncher Unit-A1 (for External Finishers)
- Platen Cover Type-W

SPECIFICATIONS

Main Unit

Type

Monochrome Laser Multifunctional

Core Functions

Standard: Print, Copy, Scan, Send, Store
Optional: Fax

Processor

Canon Dual Custom Processor (Shared)

Control Panel

10.1" TFT LCD WSVGA Color Touch-panel

Memory

3.0 GB RAM

Hard Disk Drive

Standard: 250 GB
Maximum: 1 TB

Print Resolution

1200 dpi x 1200 dpi

Interface Connection

Network

Standard: 1000Base-T/100Base-TX/10Base-T,
Wireless LAN (IEEE 802.11 b/g/n)

Optional: NFC, Bluetooth Low Energy

Others

Standard: USB 2.0 x2 (Host), USB 3.0 x1 (Host),
USB 2.0 x1 (Device)

Optional: Serial Interface, Copy Control Interface

Paper Capacity (LTR, 20 lb. Bond)

Standard: 1,200 Sheets
Maximum: 6,350 Sheets

Paper Sources (LTR, 20 lb. Bond)

Standard: Two 550-sheet Paper Cassettes,
100-sheet Stack Bypass

Optional: Two 550-sheet Paper Cassettes (Cassette
Feeding Unit-AN1), 2,450-sheet Paper Deck
(High Capacity Cassette Feeding Unit-B1),
2,700-sheet Paper Deck (Paper Deck
Unit-F1)

Paper Output Capacity (LTR, 20 lb. Bond)

Standard: 250 Sheets
Maximum: 3,350 Sheets (with External Finishers)

Finishing Capabilities

Standard: Collate, Group
With Inner Collate, Group, Offset, Staple,
Finisher: Hole Punch,* Staple-Free Staple,
Staple On Demand

With External Collate, Group, Offset, Staple, Booklet,*
Finisher: Staple-Free Staple, Staple On Demand,
Hole Punch⁶

Supported Media Types

Paper Thin, Plain, Recycled, Color, Heavy,
Cassettes: Pre-punched
Stack Bypass: Thin, Plain, Recycled, Color, Heavy,
Pre-punched, Bond, Transparency,
Label, Envelope

Supported Media Sizes

Paper Legal, Letter, Letter-R, Executive,
Cassette (1): Statement-R, Custom Size
(5-1/2" x 7-1/8" to 11-3/4" x 15-3/8")
Paper 11" x 17", Legal, Letter, Letter-R, Executive,
Cassette (2): Statement-R, Custom Size
(5-1/2" x 7-1/8" to 11-3/4" x 17")
Stack Bypass: 11" x 17", Legal, Letter, Executive,
Statement-R, Envelope [No.10 (COM10),
Monarch, DL, ISO-C5], Custom Size (3-7/8" x
5-7/8" to 11-3/4" x 17")

Supported Media Weights

Paper Cassettes: 16 lb. Bond to 34 lb. Bond (60 to 128 g/m²)
Stack Bypass: 14 lb. Bond to 80 lb. Cover (52 to 220 g/m²)
Duplexing: 16 lb. Bond to 28 lb. Bond (60 to 105 g/m²)

Warm-up Time

From Power On: Approx. 24 Seconds⁷

From Sleep

Mode: Approx. 10 Seconds⁸

Quick Startup

Mode: Approx. 4 Seconds⁹

Dimensions (W x D x H)

23-1/8" x 29-1/8" x 47" (587 mm x 740 mm x 1,193 mm)¹⁰

Installation Space (W x D)

Basic [With DADF (Stack Bypass and Cassette Drawers
Open)]: 35" x 46-1/2" (889 mm x 1,182 mm)
Fully Configured [With ADF+Paper Deck Unit-F1+
Booklet Finisher-Y1 (Cassette Drawers Open)]:
71-3/8" x 50-3/8" (1,811 mm x 1,280 mm)

Weight

Approx. 240.3 lb. (109 kg)¹¹

Print Specifications

Print Speed

4551i III: Up to 51 ppm (Letter); Up to 37 ppm
(Letter-R); Up to 25 ppm (Legal);
Up to 25 ppm (11" x 17")
4545i III: Up to 45 ppm (Letter); Up to 32 ppm
(Letter-R); Up to 25 ppm (Legal);
Up to 22 ppm (11" x 17")
4535i III: Up to 35 ppm (Letter); Up to 32 ppm
(Letter-R); Up to 25 ppm (Legal);
Up to 22 ppm (11" x 17")
4525i III: Up to 25 ppm (Letter); Up to 17 ppm
(Letter-R); Up to 13 ppm (Legal); Up to
15 ppm (11" x 17")

Standard Page Description Languages

UFR II, PCL[®]6, Adobe[®] PS[®]3

Direct Print

Available from USB, Advanced Box, Remote UI,
and Web Access¹²

Supported File Types for Direct Print

PDF, TIFF, JPEG, EPS, XPS

Fonts

PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts,
Andalé Mono WT J/K/S/T (Japanese,
Korean, Simplified and Traditional Chinese),¹³
Barcode Fonts¹⁴
PS fonts: 136 Roman

Operating System¹⁵

UFR II: Windows Server 2008/Windows[®] 7/Server
2008 R2/Server 2012/Windows 8.1/Server
2012 R2/Windows 10/Server 2016, MAC OS
X (10.9 or later)
PCL: Windows Server 2008/Windows 7/Server
2008 R2/Server 2012/Server 2012 R2/
Windows 10/Server 2016
PS: Windows Server 2008/Windows 7/Server
2008 R2/Server 2012/Windows 8.1/Server
2012 R2/Windows 10/Server 2016, MAC OS
X (10.9 or later)
PPD: MAC OS X (10.3.9 or later), Windows 7/
Windows 8/Windows 8.1/Windows 10

Copy Specifications

Copy Speed

4551i III: Up to 51 ppm (Letter); Up to 37 ppm
(Letter-R); Up to 25 ppm (Legal);
Up to 25 ppm (11" x 17")
4545i III: Up to 45 ppm (Letter); Up to 32 ppm
(Letter-R); Up to 25 ppm (Legal);
Up to 22 ppm (11" x 17")
4535i III: Up to 35 ppm (Letter); Up to 32 ppm
(Letter-R); Up to 25 ppm (Legal);
Up to 22 ppm (11" x 17")
4525i III: Up to 25 ppm (Letter); Up to 17 ppm
(Letter-R); Up to 13 ppm (Legal); Up to
15 ppm (11" x 17")

First-Copy-Out Time (Letter)

4551i III: As fast as 3.7 seconds
4545i III: As fast as 3.8 seconds
4535i III: As fast as 3.8 seconds
4525i III: As fast as 5.2 seconds

Copy Resolution (dpi)

Reading: Up to 600 x 600
Printing: 1200 x 1200

Multiple Copies

Up to 9,999 Copies

Copy Exposure

Automatic or Manual (9 Levels)

Magnification

25%-400% (1% Increments)

Preset Reductions

25%, 50%, 64%, 73%, 78%

Preset Enlargements

121%, 129%, 200%, 400%

Basic Copy Features

Preset Reduction/Enlargement Ratios by Area, Paper
Setting, Previous Settings, Favorite Settings, Finishing,
Two-Sided, Density Adjustment, Original Type Selection,
Interrupt Mode, Setting Confirmation/Cancel

Special Copy Features

Book to Two Pages, Two-sided Original, Finishing, Booklet,
Job Build, N on 1, Add Cover, Insert Sheets, Different-size
Originals, Density Adjustment, Original Type Selection,
Transparency Cover Sheets, Page Numbering, Copy Set
Numbering, Sharpness, Erase Frame, Secure Watermark,
Print Date, Shift, Gutter, Print & Check, Negative/Positive,
Repeat Images, Merge Job Blocks, Job Done Notice, Mirror
Image, Store in Mail Box, Superimpose Image, Cascade
Copy, Copy ID Card, Detect Feeder Multi Sheet Feed,
Free Size Original

Scan Specifications

Type

4551i III/4545i III: Standard Single Pass Duplexing Automatic
Document Feeder
4535i III/4525i III: Optional Single Pass Duplexing Automatic
Document Feeder or Duplexing Automatic
Document Feeder or Platen Cover

Document Feeder Paper Capacity

Single Pass DADF-A1: 150 Sheets (20 lb. Bond)
DADF-AV1: 100 Sheets (20 lb. Bond)

Document Feeder Supported Media Sizes

11" x 17", Legal, Letter, Letter-R, Statement, Statement-R

Document Feeder Supported Media Weights

Single Pass DADF-A1
BW Original: 13 lb. Bond to 58 lb. Cover
(50 to 157 g/m²)
CL Original: 17 lb. Bond to 58 lb. Cover
(64 to 157 g/m²)

DADF-AV1

BW Original: 13 lb. Bond to 34 lb. Bond
(50 to 128 g/m²)
CL Original: 17 lb. Bond to 34 lb. Bond
(64 to 128 g/m²)

Platen Acceptable Originals

Sheet, Book, 3-Dimensional Objects [Height: Up to 2"
(50mm); Up to 4.4 lb. (2 kg)]

Platen Supported Media Size

Max. scanning size: 11-3/4" x 17" (297 x 431.8 mm)

Pull Scan

Color Network ScanGear2 for both Twain and WIA
Supported OS: Windows 7/8.1/10
Windows Server 2008/Server 2008 R2/
Server 2012/Server 2012 R2/Server 2016

Scan Resolution (dpi)

600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200,
200 x 100, 150 x 150, 100 x 100

Scan Speed (Letter)

Single Pass DADF-A1
Single-sided Scanning
BW: 80 ipm (300 dpi)/80 ipm (600 dpi)
Color: 80 ipm (300 dpi)
Double-sided Scanning
BW: 160 ipm (300 dpi)/150 ipm (600 dpi)
Color: 160 ipm (300 dpi)

DADF-AV1

Single-sided Scanning
BW: 70 ipm (300 dpi)/51 ipm (600 dpi)
Color: 70 ipm (300 dpi)
Double-sided Scanning
BW: 35 ipm (300 dpi)/25.5 ipm (600 dpi)
Color: 35 ipm (300 dpi)

Send Specifications

Destination

Email/Internet Fax (SMTP), SMB v3.0, FTP, WebDAV, Mail
Box, Super G3 Fax (Optional), IP Fax (Optional)

Address Book

LDAP (2,000)/Local (1,600)/Speed dial (200)

Send Resolution (dpi)

600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200,
200 x 100, 150 x 150, 100 x 100

Communication Protocol

File: FTP (TCP/IP), SMB v3.0, WebDAV
Email: SMTP, POP3

File Format

Standard: TIFF, JPEG, PDF Device Signature
(Encrypted, Compact, Searchable,
Apply Policy, Optimize for Web, PDF A/1-b,
Device Signature), XPS (Device Signature,
Compact, Searchable), Office Open XML
(PowerPoint®, Word)
Optional: PDF (User Signature, Trace & Smooth), XPS
(User Signature)

Universal Send Features

Original Type Selection, Two-sided Original, Book to Two Pages,
Different-size Originals, Density Adjustment, Sharpness, Copy
Ratio, Erase Frame, Job Build, Delayed Send, Preview, Job Done
Notice, File Name, Subject/Message, Reply-to, Email Priority,
TX Report, Original Content Orientation, Skip Blank Originals,
Detect Feeder Multi Sheet Feed

Fax Specifications (Optional)

Maximum Number of Connection Lines

4

Modem Speed

Super G3: 33.6 Kbps
G3: 14.4 Kbps

Compression Method

MH, MR, MMR, JBIG

Resolution (dpi)

400 x 400, 200 x 400, 200 x 200, 200 x 100

Sending/Recording Size

Statement-R to 11" x 17"

Fax Memory

Up to 30,000 Pages

Speed Dials

Max. 200

Group Dials/Destinations

Max. 199 Dials

Sequential Broadcast

Max. 256 Addresses

Memory Backup

Yes

Fax Features

Original Type Selection, Two-sided Original, Book to Two
Pages, Different-size Originals, Density for Scanning,
Sharpness, Copy Ratio, Erase Frame, Job Build, Sender's
Name (TTI), Select Line, Selecting the Telephone Line, Direct
Send, Delayed Send, Preview, Job Done Notice, TX Report,
Detect Feeder Multi Sheet Feed

Store Specifications

Mail Box (Number Supported)

100 User In-boxes, 1 Memory RX In-box, 50 Confidential Fax
In-boxes, 30,000 Maximum Pages Stored

Advanced Box

Communication Protocol: SMB or WebDAV
Supported
Client PC: Windows (Windows 7/8.1/10)
Concurrent Connections (Max.)
SMB: 64
WebDAV: 3 (Active Sessions)

Advanced Box Available Disk Space

Approx. 16 GB (Standard HDD)
Approx. 480 GB (With Optional 1 TB HDD)

Advanced Box Features

Authentication for Advanced Box Log-in, Sort Function,
Printing a PDF File with a Password, imageWARE Secure
Audit Manager Support

Memory Media

Standard: USB

Security Specifications

Authentication

Standard: Universal Login Manager, uniFLOW
Online Express,¹⁶ User Authentication,
Department ID Authentication,
Access Management System,
Device and Function Level Log-in
Optional: uniFLOW

Data

Standard: Trusted Platform Module (TPM),
Hard Disk Password Lock, Hard Disk
Drive Erase, Mail Box Password Protection,
Hard Disk Drive Encryption (FIPS140-2
Validated), Verify System at Startup
Optional: Hard Disk Drive Mirroring, Hard Disk Drive
removal, IEEE 2600.2 Common Criteria
Certification, Data Loss Prevention
(Requires uniFLOW)

Network

Standard: Encrypted Secure Print, IP/Mac
Address Filtering, IPsec, TLS Encrypted
Communication, SNMP V3.0, IEEE
802.1X, IPv6, SMTP Authentication, POP
Authentication before SMTP, S/MIME,
SIEM Integration

Document

Standard: Secure Watermark, Secure Print,
Forced Hold Printing, Adobe LiveCycle®
Rights Management ES2.5 Integration,
Encrypted PDF, Encrypted Secure
Print, Device Signatures
Optional: User Signatures, Document Scan Lock

Environmental Specifications

Operating Environment

Temperature: 50 to 86°F
Humidity: 20 to 80% RH (Relative Humidity)

Power Requirements

455i III: 120-127 V AC, 60 Hz, 10.4A
4545i III/4535i III: 120-127 V AC, 60 Hz, 9.3A
4525i III: 120-127 V AC, 60 Hz, 7A

Plug (Main Unit)

NEMA 5-15P

Power Consumption

Maximum: Approx. 1,500 W
Standby: Approx. 38 W¹⁷
Sleep Mode: Approx. 0.9 W¹⁸
Typical Electricity Consumption (TEC) Rating:
455i III: 2.5 kWh
4545i III: 2.2 kWh
4535i III: 1.8 kWh
4525i III: 1.0 kWh

Standards

ENERGY STAR® Certified
Rated EPEAT® Gold³

Consumables

Toner

GPR-57 Toner BK

Toner Yield (Estimated @ 6% Coverage)

Black: 42,100 Images

- ¹ Subscription to a third-party cloud service required. Subject to third-party cloud service provider's terms and conditions.
- ² Requires additional option.
- ³ For current EPEAT rating (Gold/Silver/Bronze), please visit www.epeat.net.
- ⁴ Requires the optional Inner 2/3 Hole Puncher-C1.
- ⁵ Booklet Finisher-Y1 only.
- ⁶ Requires the optional 2/3 Hole Puncher Unit-A1.
- ⁷ Time from device power-on, until copy ready (not print reservation).
- ⁸ Time from exiting Sleep Mode to when printings is operational.
- ⁹ Time from device power-on to when key orientations can be performed on the touch panel display.
- ¹⁰ Includes Main Unit, Single Pass DADF-A1, and Cassette Feeding Unit-AN1.
- ¹¹ Includes Main Unit, Single Pass DADF-A1, Cassette Feeding Unit-AN1, and consumables.
- ¹² PDF print from Web sites is supported.
- ¹³ Requires the optional PCL International Font Set-A1.
- ¹⁴ Requires the optional Barcode Printer Kit-D1.
- ¹⁵ Other operating systems and environments including AS/400, UNIX, Linux and Citrix may be supported. Some of these solutions are chargeable. SAP Device Types are available via the SAP Market Place. For more information, contact your sales representative.
- ¹⁶ No charge for this solution; however activation is required.
- ¹⁷ Reference Value (measured one unit).
- ¹⁸ 0.9 W sleep mode not available in all circumstances due to certain settings.

For detailed specifications and a comprehensive list of optional accessories, see the imageRUNNER ADVANCE 4500i III Series Specifications document.

USA.CANON.COM/SIMPLYADVANCED



As an ENERGY STAR® Partner, Canon U.S.A., Inc. has certified these models as meeting the ENERGY STAR energy efficiency criteria through an EPA recognized certification body. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. AirPrint and the AirPrint logo are trademarks of Apple Inc. Canon, imageRUNNER, imageWARE, imagePASS, and the GENUINE logo are registered trademarks or trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. Canon products offer certain security features, yet many variables can impact the security of your devices and data. Canon does not warrant that use of its features will prevent security issues. Nothing herein should be construed as legal or regulatory advice concerning applicable laws; customers must have their own qualified counsel determine the feasibility of a solution as it relates to regulatory and statutory compliance. All other referenced product names and marks are trademarks of their respective owners. All printer output images are simulated. All features presented in this brochure may not apply to all Series and/or products and may be optional; please check with your Canon Authorized Dealer for details. Products shown with optional accessories. Canon U.S.A. does not provide legal counsel or regulatory compliance consultancy, including without limitation, Sarbanes-Oxley, HIPAA, GLBA, Check 21 or the USA Patriot Act. Each customer must have its own qualified counsel determine the advisability of a particular solution as it relates to regulatory and statutory compliance. Specifications and availability subject to change without notice. Not responsible for typographical errors.
©2019 Canon U.S.A., Inc. All rights reserved.

0216W231
0119-iRA4500IIISRSB-6M-DIH

To learn about Canon's many awards, visit
usa.canon.com/awards.

